

Model Compression via ISLE and RuleLearner®

This guide elaborates on powerful ways to combine the TreeNet[®] and GPS engines to achieve model compression and more.



© 2018 by Minitab Inc. All rights reserved.

Minitab[®], SPM[®], SPM Salford Predictive Modeler[®], Salford Predictive Modeler[®], Random Forests[®], CART[®], TreeNet[®], MARS[®], RuleLearner[®], and the Minitab logo are registered trademarks of Minitab, Inc. in the United States and other countries. Additional trademarks of Minitab, Inc. can be found at <u>www.minitab.com</u>. All other marks referenced remain the property of their respective owners.



Background and Motivation

The principal idea behind model compression is that it may be possible to use modern regression techniques to post-process a complex model to create a radically simplified version that can perform almost as well as the original. It can go even further: if you build the original complex model in a specific way there is an excellent chance that the post-processed simplified model will perform even better than the best possible complex model!

Model compression is important for several reasons:

- Compressed models can perform dramatically faster in scoring. For real time scoring compression may be the only way to feasibly deploy a high performance TreeNet[®].
- Compressed models may use many fewer predictors; compression may thus offer an alternative way to accomplish feature selection.
- Compression may provide models that are easier to explain using the component trees.

In this chapter we will cover model compression basics and try to explain why it can be expected to work. To begin, you need to understand that any model compression is a four stage process.

First, we use one of our essential data mining engines to build a predictive model. The engine could be CART[®], MARS[®], TreeNet[®], or Random Forests[®].

Second, we use the predictive model obtained to convert the original data (train and test partitions) into a new transformed version of the data.

Third, we use a regularized regression (GPS) to build a new model using the transformed data.

Finally, we extract a new compressed version of the original model.

✓ In our first release of model compression the first stage model must be a TreeNet, but in later releases the other engines can be used instead.

To understand how to work with model compression you need to have a basic grasp of working with the GPS regularized regression engine described earlier. If you have not already done so, please review those basics as we will assume this understanding in the discussion that follows.

The second step above requires further elaboration as there are several possible ways to re-express a TreeNet model into a linear combination of components later to be fed into the GPS engine for compression purposes. Two fundamentally different approaches arise here, one is called *ISLE* and the other is called *RuleLearner*[®]. We start by explaining the first one and then follow up with the second.

ISLE is an acronym for *Importance Sampled Learning Ensembles*, introduced by Jerome Friedman with co-author Bogdan Popescu in 2003.

✓ The technical paper is available on our website at http://www.salford-systems.com

While the ISLE approach has a far reaching theoretical setup, for all practical purposes it can be introduced as decomposing a TreeNet model into a set of variable transformations represented by each individual tree in that model. This stems from a simple observation that any tree can be viewed as a potentially multivariate transformation of the original predictors. This is illustrated below.





One can therefore represent any TreeNet model as a linear combination of individual tree variables with coefficients 1.0.

 This assumes that the learn rate and initial guess adjustments were incorporated into the trees, which is trivial to do.

Thus, after these variables have been fed as inputs to the GPS engine, a new linear combination will have different coefficients. Given the GPS's inherent ability to do variable extraction by trying different variable selection strategies (elasticities), a fraction of predictors may have zero coefficients which in this context is equivalent to removing the corresponding tree from the model thus achieving model compression. As an added bonus, it is possible that the new model will have superior performance.



The ISLE compression is visualized on the next diagram.

Note how some trees have been eliminated (zero coefficients) while the others were adjusted to provide the best fit.

Another way to think about the model compression is to recall that a TreeNet model is an ensemble model consisting of many small CART-style decision trees. Each tree produces an output "score", and the final model is simply the grand total of all the individual scores. Usually TreeNet approaches its final result slowly, with each tree contributing a small part of the final model result. When we "compress" the



TreeNet model via GPS regression we select a subset of these trees and reweight them in order to arrive at a model which has fewer trees and possibly better performance as well. The abstract technical mechanism by which this is accomplished is best understood by studying GPS; here we provide an intuitive explanation for what is going on.

A TreeNet model is built myopically, looking only one step ahead as the model is built tree-by-tree. To obtain good results, each step is small, meaning that each tree can add only a very small amount to the overall TreeNet prediction. When the TreeNet model is complete we typically have very many of these trees and there is an excellent chance that some tree structures are repeated exactly, or almost exactly. The compression phase can then work as follows:

- Identical or almost identical trees can be aggregated into just one tree with an appropriate weight. If the same tree was grown 20 times we could replace these trees with just one tree and provide it with a weight of 20. In real world modeling the trees may differ in details which make exact reproduction in this way impossible, but we may be able to produce a very close approximation.
- When the TreeNet model is grown we do not know what the next tree will bring and in the process of arriving at final scores there may be some oscillation around a final solution or even backtracking in which some trees are essentially cancelled out of the final result. Once the model has been constructed we can accomplish any "cancelling out" by simply deleting trees and we can skip over any oscillations. The end result will be a smaller collection of trees.

The final result of the ISLE Model compression is a smaller model of the same type we started with. In this case, we always start with a TreeNet and we end up with a TreeNet. But the new TreeNet has fewer trees and each tree has its own weight which could be far different than 1.0!

The second approach (here introduced as the **RuleLearner**) of decomposing a TreeNet model into individual derived variables is introduced by pushing the decomposition process further down, all the way to the individual nodes. Observe that any tree spawns a set of dummy variables, one variable per each terminal and internal node.



The only exception is the root node which includes the entire sample and would result to a trivial constant dummy variable.



Thus the complete set of node dummies represents all structural information contained in any TreeNet model. Note that the set is overrepresented, internal nodes largely overlap with their parents and completely include their children. This opens up even greater opportunities for possible model simplification by identifying the subset of influential nodes and finding coefficient adjustments associated with each node such that the original model fit is essentially recovered. Again, just as in the case of ISLE approach, the GPS regularized regression engine is perfectly suited for this task. Furthermore, it is possible that the resulting model may achieve higher performance compared to the original TreeNet model while maintaining an excellent compression ratio.

This process is illustrated on the following diagram.



Observe that each node dummy represents a collection of rules in terms of the original predictors leading into this node. Therefore, another way to look at this type of compression is in terms of extracting a collection of informative rule-sets (segments). Each rule-set operates on a subset of data or, to paraphrase, each rule-set represents a segment of the data. The regression coefficient assigned to this segment by the GPS is simply the segment-based adjustment to the overall model prediction. Note that segments can overlap with each other and may have either positive or negative adjustments of varying magnitude thus making the model prediction extremely versatile.

Both types of TreeNet model compression (ISLE and RuleLearner) are implemented in SPM[®]. In the following sections we describe the basic steps needed to setup model compression as well as explain various output windows produced along with the possible usage modes.



Model Compression in Action – ISLE EXAMPLE (coupled with RULELEARNER sub-example)

At this point it will suffice to say that setting up a model compression run from a user standpoint is very straightforward. We are essentially creating a "pipeline", a sequence of two already introduced engines, first a TreeNet engine using the original predictors then followed up by a GPS engine that uses decomposed TreeNet model as its own inputs. The decomposition itself is done automatically by SPM based on the user selected method, which could be either ISLE or RuleLearner (as well as additional trivial modifications introduced below). In addition, it is assumed that each engine component of the pipeline (TreeNet and GPS) is configured using its own set of control parameters as usual.

The end result of the compression pipeline is the overall compression summary plus the usual output of the TreeNet engine (as if it were run by itself) as well as the standard GPS output of the follow up compression phase.

The output displays are deliberately designed for ease of comparison between the original uncompressed model and the resulting compressed model. The user can choose any desired model for viewing, scoring, and translation using the "point and click" approach thus balancing the degree of compression versus model size.

Setting up Model Compression

We start with the GOODBAD.CSV data set which is rather on the small side but runs very quickly and illustrates our main points well. The dataset comes from a credit default study and has 664 observations and 14 variables including a binary response variable named TARGET, with 1 indicating a bad credit standing account and 0 otherwise. The remaining predictors provide a nice mix of continuous and categorical measures which represent a typical modeling environment. The goal of the study is to build a predictive model for bad credit using the TreeNet approach and then possibly compress the model using either ISLE or RuleLearner approaches.

Use the **File/Open/Data File...** menu item to open the GOODBAD.CSV dataset, then click the **[Model...]** button in the resulting activity window to open the **Model Setup** window.

In the Model tab:

- Set Analysis Engine to ISLE Model Compression this activates the pipeline part of the SPM the ISLE tab. This exercise is useful for elaborating on the RuleLearner component as well.
- ✓ Note that this mode activates the **TreeNet** tab and the **GPS** and **GPS** Advanced tabs, thus giving you full control over other parts of the pipeline.
- Set **Sort:** to **File Order** this sorts all variables according to the position in the dataset.
- Check TARGET variable as the **Target**.
- Check all remaining variables as predictors.
- Select **Target Type** to **Classification/Logistic Binary** to take advantage of the natural capability of both TreeNet and GPS engine to handle binary targets effectively.



GPS	GPS Advanced	ISI E	Cost	•	Class Weid	hts Pen	altv	Lags	1	
Model	Categorical	Testing	Select C	ases	TreeNet	Plots&	Options	TN Advanced	TN Interactions	
	· · ·			Variable Selection						
	Variable Na	ame		Target	Predictor	Categorical	Weight	Target	Type assification/	
ARGET				~		V			gistic Binary	
GE								C Re	gression	
REDIT_LI	МІТ							C Un	supervised	
DUCATIO	N\$				V					
GENDER								Set F	ocus Class	
HH_SIZE										
NCOME								Tar	aat Variabla	
MARITAL\$								TARGET		
N INQUIRI	ES				v			▼		
	den al			Select	Se	lect —		We	ight Variable	
ort: ¡File Or	der 💽			Predict	cors Ca	at.				
Filter						Numbe	Number of Predictors			
 All/Sele 	cted Character	O Numerio							13	
comatic Bes	st Predictor Discovery					Nu	mber of P	redictors in Mod	el: 13	
Off			A	fter Build	ding a Mode	An	alysis Eng	jine		
Discover o	nly Maximum va	iables	_	Save	Grove		SLE Mod	el Compressior	n <u>•</u>	
	na we fan and de	8	÷							

Switch to the Testing tab, and make sure that **Fraction of cases selected at random** for testing is set to 0.2.

We now need to set up the TreeNet component of the pipeline, as if you were setting up a stand-alone TreeNet model. Using the TreeNet tab, we set the following controls.

- Set the Learn Rate to 0.05.
- Set the **Number of trees** to 500.
- Set the Criterion Determining Number of Trees Optimal for Logistic Model to ROC area.
- Leave the remaining controls at their defaults (consult with the screenshot below).
- ✓ See the guide on TreeNet for detailed description of all of the available controls.



GPS GPS Ad Model Categ Criterior C Cre C C C Cre C C C C C C C C C C C C C C C C C C C	vanced ISLE porical Testing t Loss Function fication/Logistic Bina n Determining Numbross Entropy (Likeliho assification Accuracy ting Protection	Costs g Select Cases Treel rry T er of Trees Optimal fr od) © ROC arr , Classify cases as Ta	Class Weights TreeNet Net Options	Penalty Plots&Options given proportion of vility Exceeds	Lags TN Advanced Configure of 0.100 = 0.500 =	TN Interactions							
Model Categ	t Loss Function ification/Logistic Bina n Determining Number oss Entropy (Likelihor assification Accuracy ting Protection	g Select Cases Treel rry I General for od) © ROC are . Classify cases as Ta		Plots&Options	TN Advanced Configure	TN Interactions							
Criterior Criterior C Cro C Cla Overfitt Learr Sub Random	t Loss Function fication/Logistic Bina n Determining Number oss Entropy (Likelihou assification Accuracy ting Protection Bate: Auto	Treel	Net Options	given proportion a	Configure of 0.100								
Criterior Criterior C Cri C Cla Overfitt Learr Sub Random	t Loss Function fication/Logistic Bina n Determining Number oss Entropy (Likelihor assification Accuracy ting Protection	er of Trees Optimal fr od)	or Logistic Model ea C Lift in g arget Class if Probab	given proportion a	Configure								
Classi Criterior C Cro C Cla Overfitt Learr Sub Random	fication/Logistic Bina n Determining Numbe oss Entropy (Likeliho assification Accuracy ting Protection	er of Trees Optimal for od) • ROC are	or Logistic Model	given proportion o vility Exceeds	Configure of 0.100								
Criterior C Cro C Cla Overfitt Learn Sub Random	n Determining Number oss Entropy (Likelihor assification Accuracy ting Protection	er of Trees Optimal fo od) • ROC are	or Logistic Model ea C Lift in g arget Class if Probab	given proportion o vility Exceeds	of 0.100								
C Cro C Cla Overfitt Learn Sub Random	oss Entropy (Likeliho assification Accuracy ting Protection	od)	ea C Lift in g arget Class if Probab	given proportion o vility Exceeds	of 0.100								
C Cla Overfitt Learn Sub Random	ting Protection	. Classify cases as Ta	arget Class if Probab	ility Exceeds	0.500	3							
Overfitt Learn Sub Random	ting Protection												
Learr Sub Random Prec	n Rate: Auto	Overfitting Protection											
Sub Random		0.0500	Num	ber of trees to bu	iild: 500								
Random	osample fraction:	0.50	Maxi	mum nodes per tr	ee: 6								
Prec	n		Terminal no	de Minimum Train	ing 10	3							
	dictors per node:	6	Influence trimming speed-up										
🗌 Vary	y tree sizes randomly	y (As Poisson)	Total Influence fraction: 0.10										
I Mod sepa	del Variance-Dispersio arately	on compoment	Std. Defaults	Save Defaults	Recall Defau	lts							
utomatic Best Predictor	Discovery			Number of P	Predictors in Mode	el: 13							
Off		After	Building a Model	Analysis En	gine								
Discover only		Sa	ave Grove	ISLE Mod	el Compression	•							
Ma Discover and run for						1							

Next you may want to set up the GPS component of the pipeline using the **GPS** and **GPS** Advanced tabs. The default settings in those tabs are good enough for our purposes, you may however, review the GPS guide and later experiment with different number of steps, points, as well as elasticities and learn rates. Finally, switch to the ISLE tab to setup the actual pipeline "linkage" parameters, which could be as simple as specifying whether you want ISLE or RuleLearner compression or both (Pooled ISLE and Node Predictors).



Model Setup	×
Model Categorical Testing Select Case GPS GPS Advanced ISLE Costs	es TreeNet Plots&Options TN Advanced TN Interactions Class Weights Penalty Lags
Pure Tree-Based Models Estima Image: TreeNet Model compression (ISLE) 500 Image: RuleLearner: Extract Rules from TreeNet 5000 Image: Pool ISLE and Node Predictors 5500 Hybrid Tree-regression Models Free Rules Image: None Free Rules	Ited Predictor Counts (one predictor per tree) (one predictor per node) (both trees and nodes are predictors) Rules Reporting and Saving (RuleLearner) Max Rules to report:
$^{\rm C}$ $$ Include Original Predictors in models selected above Records with missing values will be deleted $^{\rm C}$ Run models both ways (with and without original predict	tors)
	Std. Defaults Save Defaults Recall Defaults
Automatic Best Predictor Discovery O Off Discover only Maximum variables O Discover and run for each class	Number of Predictors in Model: 13 r Building a Model Analysis Engine Save Grove ISLE Model Compression Cancel Continue

Note that we have requested both ISLE and RuleLearner which will trigger two independent compression runs after the initial TreeNet model has been built: one run to try the ISLE compression and the other to try the RuleLearner compression. This gives you the convenience of not building the TreeNet model (the first stage of the pipeline) twice and thus saving the overall run time.

The control options on the ISLE tab under the Pure Tree-Based Models section are:

- TreeNet Model Compression (ISLE) uses tree-based variables as intermediate inputs to the GPS compression stage.
- RuleLearner: Extract Rules from TreeNet uses node-based variables as intermediate inputs to the GPS compression stage.
- Pool ISLE and Node Predictors technically a hybrid approach, uses the combined set of both tree-based and node-based variables as intermediate inputs to the GPS compression stage. Note that the end result of this could be a compressed model that has both types of components.
- Estimated Predictor Counts reports the total number of intermediate variables that will be created during the pipeline process. Note that the RuleLearner approach dramatically increase the memory and computational burden of the process, use it judiciously!
- Hybrid Tree-regression Models allows to include the original predictors into the intermediate set of inputs to the GPS compression stage. This sometimes helps to compress the model even further in the presence of strong linear effects.
- Keep in mind that each pipeline mode, especially when it involves the node-based variables (RuleLearner) may take significant amount of run time. It is best to start experimenting with a single ISLE or RuleLearner model first and then proceed with more elaborate setups.
- Max Rules to Report sets the default number of the top important rules that will be reported and saved.
- [Save Results to] click this button if you want to save the top important rules into a file.



Press the [Start] button to initiate the modeling pipeline.

Depending on your prior system settings, the following window may occur:

Salford Predictive Modeler v7.0
Discrete variables were discovered that have one or more levels not encountered in all data partitions. All levels not seen in the training data are mapped to "missing" in test,
Do not show this message again.

This indicates that some of the categorical predictors available in the dataset had under-represented categories that could not be assigned to both learn and test partitions. You may ignore this warning for now and press the **[OK]** button to proceed with the modeling run.

As the run develops, you will first see the TreeNet engine progress report followed by the GPS engine progress report for the ISLE run and then again for the RuleLearner run. This indicates that the two separate pipelines are being properly executed.

Viewing Model Compression Results

A successfully finished compression run with more than one pipeline will produce the **Pipeline Results: Models** summary window shown below.





In our case, three different models are reported:

- **Original** the original best TreeNet model before compression.
- ISLE best model using ISLE (tree-based variables) compression.
- **RuleLearner** best model using RuleLearner (node-based variables) approach.

The graph area displays the currently selected performance measures for each model.

Note that the original TreeNet model had 498 trees (coefficients) while the ISLE compressed model has only 247 trees (50.40% compression rate) while improving the test sample ROC performance.

Likewise, the original TreeNet model had 4980 nodes (6-node default regression trees used by the TreeNet engine actually have 10 nodes each, counting both terminal and internal nodes and excluding the root node). The RuleLearner compressed model has 2789 selected nodes (55.77% compression rate) while improving the test sample ROC performance as well.

Thus, we have successfully accomplished the original goal of reducing the complexity of the TreeNet model by a significant amount while improving the test sample performance.

The following key controls are located on the results window:

- Charts one can switch between the [Performance] and [Coefficients] display mode of the graph.
- Chart Type one can switch between the [Bar] and [Line] style of the graph.
- [Show Optimal Performance] press this button to highlight the best performing model using green background in the table.
- **Performance Measure:** choose among a variety of different performance measures. Once a new measure is selected, all displays will be updated.
- Sample these buttons select among the learn and test data partitions.
- [Score...], [Translate...], [Commands...], [Save Grove...] these are standard action buttons available in any engine.

Scoring Compressed Model

Press the [Score...] button to activate the Score Data control window.

Use the **Select model to score:** selection box to pick the model of interest (the Original, ISLE, or RuleLearner).

Press the **[Select...]** button in the **Select Specific Model** section if you want to pick a different model on the GPS path for the current compression approach.

The rest of the scoring controls have been described earlier in the manual.

Press the **[Score]** button to initiate the scoring process.



Translating Compressed Model

Press the [Translate...] button to activate the Model Translation control window.

Model Translation		×
Grove Open Grove File Select model to transl	C:\Users\enovo\A ate: Pipeline ISLE - Bin	ppData\Local\Temp\skds_00050.grv ary Classification - Target: TARGET
Select Specific Model	sticity 2, Point #96, NCoe	ff=247, ROC (Area Under Curve): 0.906344 Optimal Select
Save Output To File	ort C Classic C History	SAS Options
C PMML C Java	C Rules C Plots C Skeleton C Topology	Begin label: MODELBEGIN Done label: MODELDONE Node prefix: NODE Terminal Node Prefix: TNODE
		Cancel OK

Use the **Select Specific Model** selection box to pick the model of interest (the Original, ISLE, or RuleLearner).

Press the **[Select...]** button in the **Select Specific Model** section if you want to pick a different model on the GPS path for the current compression approach.

The rest of the translation controls have been described earlier in the manual.

Press the **[OK]** button to initiate the model translation process.

We used the above procedure to translate the 2-tree ISLE model into SAS. An example output code would have the following layout:

```
/* Tree 2 of 276 */
tnscore = -0.844412208; /* GPS ISLE Tree Coefficients */
<Block of code representing the tree logic to generate "response" update for the
current tree>
tnscore = tnscore + 0.126800358 * response;
/* Tree 5 of 276 */
<Block of code representing the tree logic to generate "response" update for the
current tree>
tnscore = tnscore + 1.25642133 * response;
return;
```

ISLE model translation only includes trees selected by the compression method (non-zero coefficients). Observe how the new updated ISLE coefficients are introduced directly into the model code.



✓ A similar code is produced when translating a RuleLearner model. However, because the RuleLearner model decomposition takes place at the node level, there is no simple way to reduce the model code by eliminating the redundant nodes. As the interim implementation, we now produce the full original TreeNet model code with the node-level adjustments augmented for all nodes selected by the RuleLearner process. Thus the code itself produces the correct RuleLearner scores but it also includes large parts that are unnecessary. This inconvenience has now been fully resolved in the latest release of the RuleLearner component.

Viewing ISLE Model Compression Details

Double click on the ISLE row in the **Pipeline Results: Models** window. This will open the **ISLE** window reporting details of the ISLE compression run.

This window automatically opens up instead of the Pipeline Results: Models window when ISLE is the only compression method requested in the ISLE tab of the Model Setup window.



This window shows detailed ISLE compression results indexed by model size in trees. The two test sample performance curves are aligned such that one can easily compare the performance of two models with identical size. Note that the 247-tree TreeNet model has test ROC 0.885 while the 247-tree ISLE compressed model has ROC 0.906. Even though both models have identical number of trees, they differ in the actual trees. The TreeNet model takes the first 247consecutive trees from the TreeNet sequence (all combined with the unit coefficients) while the ISLE model takes some specific subset of 247 trees from the original 500 trees available in the sequence, combined with ISLE specific coefficients.

✓ The actual subset of trees can be determined by looking into the ISLE Details or translating the model.

The top part of the window reports basic stats on the optimal TreeNet model versus optimal ISLE model in terms of ROC performance.



Original TreeNet	Best Compression
Tree Size: 6	% Compression: 50.40
Trees Grown: 500	% Gain/Loss: 0.010
Trees Optimal: 498	Trees Extracted: 247
Performance: 0.89735	Performance: 0.90634

✓ You can switch to alternative performance measures using the Performance Measure: selection box.

Press the **[TreeNet Details]** button to open the usual **TreeNet Output** window described in the TreeNet engine chapter of this manual.

Press the **[ISLE Details]** button to open the usual **GPS Results** window described in the GPS engine chapter of this manual.

✓ Note that the GPS component of the ISLE pipeline uses trees as input variables. Therefore, all parts of the GPS output windows referencing the predictors (Coefficients, etc.) will now report names like Tree 1, Tree 2, Tree 3, etc.

The remaining control items are similar to what we have already described earlier.

Viewing RuleLearner Model Compression Details

Double click on the RuleLearner row in the **Pipeline Results: Models** window. This will open the **RuleLearner Results: RuleLearner** window reporting details of the RuleLearner compression run.





✓ This window automatically opens up instead of the **Pipeline Results: Models** window when RuleLearner is the only compression method requested in the **RuleLearner** tab of the **Model Setup** window.



This window shows detailed RuleLearner compression results indexed by model size in nodes. The two test sample performance curves are aligned such that one can easily compare the performance of two models with identical size.

Note that the 2789-node TreeNet model has test ROC 0.875 while the 2789-node RuleLearner compressed model has ROC 0.90584. Even though both models have identical number of nodes, they differ in the actual trees selected. The TreeNet model takes the first consecutive trees from the TreeNet sequence (all combined with the unit coefficients and the original node updates) while the RuleLearner model takes some specific subset of 2789 nodes from the original complete set available in the sequence. Furthermore, each selected node has a new associated update.

✓ The actual subset of nodes can be determined by looking into the RuleLearner Details or translating the model.

The top part of the window reports basic stats on the optimal TreeNet model versus optimal RuleLearner model in terms of ROC performance.

Original TreeNet	Best Rule Extraction
Tree Size: 6	% Compression: 55.77
Trees Grown: 500	% Gain/Loss: 0.009
Rules Optimal: 6,306	Rules Extracted: 2,789
Performance: 0.89735	Performance: 0.90584

✓ You can switch to alternative performance measures using the Performance Measure: selection box.



Press the **[TreeNet Details]** button to open the usual **TreeNet Output** window described in the TreeNet engine chapter of this manual.

Press the **[RuleLearner Details]** button to open the usual **GPS Results** window described in the GPS engine chapter of this manual.

Note that the GPS component of the RuleLearner pipeline uses nodes as input variables. Therefore, all parts of the GPS output windows referencing the predictors (Coefficients, etc.) will now report names like Tree 1 Node 1, Tree 1 TNode 1, Tree 2 Node 1, etc.

The remaining control items are similar to what we have already described earlier except for the **[Rules...]** button which opens up a RuleLearner specific **Explore** window.

Exploring the Rules

Press the [Rules...] button in the Pipeline Results: RuleLearner window to open the Explore RuleLearner window shown below.

45 100.00% 241 4 Intermediate 0.09021 Rel. Importance: 00.00% Importance: 0.0447 91 95.94% 172 4 Intermediate 0.08584 104 93.49% 203 5 Intermediate 0.08684 100 92.33% 416 2 Terminal 0.08651 147 92.22% 370 7 Intermediate 0.08251 132 92.22% 370 7 Intermediate 0.082561 135 91.62% 367 1 Terminal 0.08458 145 91.43% 133 5 Intermediate 0.08252 67 91.23% 370 4 Intermediate 0.08262 75 90.88 222 4 Intermediate 0.08262 65 68.20% 433 1 Terminal 0.08262 75 90.88 22 4 Intermediate 0.08272 75 90.88 3 Intermediate 0.08272 75 90.88 3	#	Importance \bigtriangledown	Tree Number	Node Number	Terminal		# 45	Tree:	241 Node:	Intermediate	4 Depth:	4	
43 100.002 241 4 Intermediate 0.00024 104 93.94% 203 5 Intermediate 0.08954 104 93.93% 203 5 Intermediate 0.08954 100 92.33% 416 2 Terminal 0.08254 107 92.93% 333 2 Intermediate 0.08254 107 91.95% 315 1 Terminal 0.08262 107 91.52% 227 4 Intermediate 0.08257 135 91.52% 227 4 Intermediate 0.08262 151 91.32% 115 6 Terminal 0.08262 75 90.68% 222 4 Intermediate 0.08262 75 90.68% 222 4 Intermediate 0.08262 75 90.68% 222 4 Intermediate 0.08262 109 88.67% 446 7 Terminal 0.08262 194 80.01% 88 3 Intermediate 0.08076 <	45	100.00%	241	4	Intermediate	0.00021	Coefficient:	0.09021	Rel. Importance:	100.00% In	portance:	0.0447	
31 33.94% 112 4 Intermediate 0.0034% 104 93.49% 20 5 Intermediate 0.0034% 100 92.33% 416 2 Terminal 0.008261 132 92.22% 339 2 Intermediate 0.008261 132 92.22% 370 7 Intermediate 0.08236 135 91.62% 367 1 Terminal 0.08236 96 91.52% 227 4 Intermediate 0.08236 975 91.62% 37 1 Terminal 0.08236 67 91.22% 37 4 Intermediate 0.08236 56 99.20% 313 5 Intermediate 0.08270 103 69.872% 446 7 Terminal 0.08286 56 69.20% 313 5 Intermediate 0.08270 146 88.75% 446 7 Terminal 0.08286 146 88.75% 499 5 Intermediate 0.08175	40	05.04%	241	4	Intermediate	0.03021							
104 33.43% 203 3 Intermediate 0.08511 100 92.33% 416 2 Terminal 0.08511 147 92.23% 333 2 Intermediate 0.08511 132 92.22% 370 7 Intermediate 0.08252 135 91.62% 367 1 Terminal 0.082537 145 91.43% 183 5 Intermediate 0.08252 151 91.23% 175 6 Terminal 0.08262 151 91.23% 135 1 Terminal 0.08262 155 91.23% 135 1 Intermediate 0.08270 109 98.97% 29 3 Intermediate 0.08282 109 98.97% 29 3 Intermediate 0.08280 146 98.02% 446 7 Terminal 0.08282 146 88.02% 409 1 Terminal 0.08282 151 91.25456 1.19064 1.19064 144 88.01% 88 3 Intermediate 0.08176 144 88.01% 4 Intermediate 0.08037 131	104	33.34%	202	4	Intermediate	0.00304	POSTRINIS	2 50000 a	POSTRIN is missing				
100 33.33 416 2 Terminal -0.08261 147 92.23% 370 7 Intermediate 0.082261 132 92.22% 370 7 Intermediate 0.082361 135 91.62% 315 1 Terminal 0.082361 36 91.52% 227 4 Intermediate 0.08236 36 91.52% 227 4 Intermediate 0.08236 15 91.33% 115 6 Terminal 0.08236 67 91.12% 370 4 Intermediate 0.08236 75 90.68% 222 4 Intermediate 0.08230 210 88.67% 246 7 Terminal 0.08262 146 88.25% 409 1 Terminal 0.08262 146 87.76% 99 5 Intermediate 0.07334 1314 87.30% 13 1 Terminal 0.08282 62 86.42% 175 5 Intermediate 0.07334 1 </td <td>104</td> <td>33.43%</td> <td>203</td> <td>2</td> <td>Intermediate</td> <td>0.08436</td> <td>OCCUP BLA</td> <td>NK < 0.50</td> <td>000 and OCCUP BLAN</td> <td>K is not missing</td> <td></td> <td></td> <td></td>	104	33.43%	203	2	Intermediate	0.08436	OCCUP BLA	NK < 0.50	000 and OCCUP BLAN	K is not missing			
147 32.23% 333 2 Intermediate 0.08239 132 92.22% 370 7 Intermediate 0.08239 107 91.95% 315 1 Terminal 0.08288 135 91.62% 367 1 Terminal 0.08288 36 91.52% 227 4 Intermediate 0.08282 135 91.62% 370 4 Intermediate 0.08282 151 91.23% 370 4 Intermediate 0.08282 167 91.12% 370 4 Intermediate 0.08282 75 90.68% 222 4 Intermediate 0.08270 109 88.67% 446 7 Terminal 0.08282 114 88.01% 88 3 Intermediate 0.08930 114 88.01% 488 3 Intermediate 0.08734 128 87.44% 446 4 Intermediate 0.07911 131 95 5 5 0.38006 5 <tr< td=""><td>147</td><td>32.33%</td><td>410</td><td>2</td><td>latama diata</td><td>0.00001</td><td>GENDER is</td><td>not missing</td><td></td><td></td><td></td><td></td><td></td></tr<>	147	32.33%	410	2	latama diata	0.00001	GENDER is	not missing					
102 32.22% 370 7 Intermediate 0.008468 107 91.95% 315 1 Terminal 0.008288 135 91.62% 367 1 Terminal 0.008288 96 91.52% 227 4 Intermediate 0.008262 151 91.23% 115 6 Terminal 0.008266 67 91.28% 370 4 Intermediate 0.008206 109 88.67% 22 4 Intermediate 0.008201 109 88.67% 29 3 Intermediate 0.008201 109 88.67% 46 7 Terminal 0.008300 114 88.01% 88 3 Intermediate 0.008120 114 88.01% 88 3 Intermediate 0.008176 114 87.70% 99 5 Intermediate 0.008126 114 87.74% 486 4 Intermediate 0.008126 128 87.74% 486 4 Intermediate 0.008224<	197	32.23%	333	2	Intermediate	0.00201							
107 31:33.4 313 1 Terminal -0.08288 35 91:52% 227 4 Intermediate -0.08238 36 91:52% 227 4 Intermediate -0.08238 145 91:43% 118 5 Intermediate -0.08236 67 91:12% 370 4 Intermediate -0.08220 75 90:68% 222 4 Intermediate -0.08220 75 90:68% 222 4 Intermediate -0.08820 210 88.67% 246 7 Terminal -0.08890 210 88.67% 446 7 Terminal -0.08890 146 88.25% 409 1 Terminal -0.08282 146 87.76% 99 5 Intermediate 0.07314 141 87.30% 193 1 Terminal -0.08282 152 86.643% 196 6 Intermediate -0.07314 141 87.30% 193 1 Terminal -0.08282	107	32.22%	370	1	Transie	-0.00232							
133 3162.4 367 1 <td< td=""><td>107</td><td>31.33%</td><td>310</td><td></td><td>Terminal</td><td>-0.00400</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>	107	31.33%	310		Terminal	-0.00400							
36 37,32,2 227 4 Intermediate 0.08236 145 91,433 183 5 Intermediate 0.08236 151 91,233 115 6 Terminal 0.08236 67 91,128 370 4 Intermediate 0.08236 75 90,683 222 4 Intermediate 0.08445 56 83,07% 29 3 Intermediate 0.08930 109 88,67% 446 7 Terminal 0.08930 146 88,25% 409 1 Terminal 0.08622 148 87,76% 99 5 Intermediate 0.08176 148 87,74% 485 4 Intermediate 0.08176 141 87,30% 193 1 Terminal -0.08282 62 86,82% 195 6 Intermediate -0.07931 133 86,61% 328 4 -0.08282 -0.50002 0.49099 141 87,90% 29 6 6 Intermedia	155	01.02%	307	4	Intermediate	0.00200							
Instant Instant Instant Intermediate Intermediate<	145	01.02%	100	4	Intermediate	0.00007							
131 31/23* 113 6 Intermediate 0.08821 75 90.68% 222 4 Intermediate 0.08821 75 90.68% 222 4 Intermediate 0.08821 109 88.87% 28 3 Intermediate 0.08900 210 88.67% 446 7 Terminal 0.07933 57 88.52% 409 1 Terminal 0.08262 114 88.01% 88 3 Intermediate 0.08176 144 88.01% 88 3 Intermediate 0.07911 231 87.54% 146 4 Intermediate 0.07911 231 87.54% 146 4 Intermediate 0.07911 231 87.54% 146 4 Intermediate 0.08282 62 86.84% 196 6 Intermediate 0.08283 141 87.56% 229 3 Intermediate 0.08024 161 85.56% 2275 4 Intermediate 0.08024	143	01.43%	115		Terminal	0.00202							
bit 37 370 4 Intermediate 0.008720 109 89.87% 29 3 Intermediate 0.008720 109 89.87% 29 3 Intermediate 0.008720 109 89.87% 29 3 Intermediate 0.00845 56 89.20% 313 5 Intermediate 0.00890 110 88.67% 446 7 Terminal 0.00890 146 88.25% 409 1 Terminal 0.008262 1164 87.76% 99 5 Intermediate 0.008176 1164 87.76% 99 5 Intermediate 0.008176 1218 87.74% 485 4 Intermediate 0.00731 1231 87.54% 146 4 Intermediate 0.008282 62 86.42% 196 6 Intermediate 0.00873 193 86.51% 328 4 Intermediate 0.008074 161 85.96% 229 3 Intermediate 0.008	101	01.23%	270	0	Intermediate	-0.00230							1
13 3003-5 222 4 Intermediate 0.00120 19 88.87% 23 3 Intermediate 0.00245 56 89.20% 313 5 Intermediate 0.00245 210 88.67% 446 7 Terminal 0.00280 146 88.25% 409 1 Terminal 0.00262 164 87.76% 99 5 Intermediate 0.00215 218 87.74% 485 4 Intermediate 0.07111 231 87.54% 193 1 Terminal 0.002822 62 86.64% 196 6 Intermediate 0.07111 141 87.30% 193 1 Terminal 0.002822 62 86.64% 196 6 Intermediate 0.00823 193 96.51% 328 4 Intermediate 0.008024 161 85.96% 229 3 Intermediate 0.008024 114 85.95% 229 3 Intermediate 0.008024	75	90.00%	370	4	Intermediate	0.00021						Prev	N
100 0007% 1.0 0 56 88.20% 31 5 Intermediate 0.08900 210 88.67% 446 7 Terminal 0.07930 57 88.52% 409 1 Terminal 0.08930 146 88.25% 409 1 Terminal 0.08920 146 88.25% 409 1 Terminal 0.08262 194 80.01% 88 3 Intermediate 0.08176 218 87.74% 485 4 Intermediate 0.07911 231 87.54% 146 4 Intermediate 0.07911 231 87.54% 195 6 Intermediate 0.08282 62 86.84% 196 6 Intermediate 0.08293 133 86.51% 328 4 Intermediate 0.08024 161 85.95% 2275 4 Intermediate 0.08178 1114 85.95% 229 3 Intermediate 0.08179	109	00.00%	222	4	Intermediate	0.09445							
Job Display Display Display Display 100 88 67% 445 7 Terminal 0.07933 157 88 52% 409 1 Terminal 0.08890 146 88 25% 409 1 Terminal 0.08807 146 88 25% 409 1 Terminal 0.08807 146 88 01% 88 3 Intermediate 0.080176 148 87.74% 485 4 Intermediate 0.07934 141 87.30% 193 1 Terminal -0.08282 62 86.62% 179 5 Terminal -0.08283 141 87.30% 226 6 Intermediate -0.08039 133 86.61% 328 4 Intermediate -0.08039 133 386.51% 328 4 Intermediate -0.08039 133 86.51% 328 4 Intermediate -0.08039 141 85.95% 2275 4 Intermediate -0.08039 114 85.95% 229 3 Intermediate -0.08049	EC	00.07%	23	5	Intermediate	0.00443							_
210 0001/2 440 7 Terminal 0.00890 145 88.25% 409 1 Terminal 0.00890 146 88.25% 409 1 Terminal 0.00890 146 88.25% 409 1 Terminal 0.00812 157 88.52% 409 1 Terminal 0.00825 164 87.76% 99 5 Intermediate 0.00815 218 87.74% 485 4 Intermediate 0.0711 231 87.54% 146 4 Intermediate 0.0711 231 87.54% 146 4 Intermediate 0.0711 141 87.30% 193 1 Terminal 0.00822 52 86.64% 196 6 Intermediate 0.00823 153 328 4 Intermediate 0.00824 161 85.56% 2.275 4 Intermediate 0.008074 114 85.95% 2.29 3 Intermediate 0.008078 11	210	00.20%	446	7	Torminal	0.00000	11		Learn	Test			
37 0002/2 433 1 Terminal 0002/2 0.432/3 0.432/3 0.432/3 146 88/25 409 1 Terminal 0.002/2 0.432/3 0.432/3 0.432/3 146 88/25 409 1 Terminal 0.002/2 0.432/3 0.432/3 0.432/3 146 88/25 409 1 Terminal 0.002/2 0.432/3 0.432/3 0.432/3 164 87/24% 99 5 Intermediate 0.00176 N 223 67 231 87/54% 146 4 Intermediate 0.07911 Std. Dev. 0.50002 0.43099 231 87/54% 146 4 Intermediate 0.0832 Std. Dev. 0.50002 0.43099 32 86.62% 179 5 Terminal -0.08282 Std. Dev. 0.50002 0.43099 3133 86.51% 328 4 Intermediate -0.08024 Std. Dev. 0.50002 0.43099 161 85.96% 275 4 Intermediate <	57	00.07%	440	1	Terminal	.0.09990	C	. –	0.40000		0.49630		
Indem Observation Indem Observation Indem 194 88 01% 88 3 Intermediate 0.08015 194 87.76% 99 5 Intermediate 0.08016 218 87.74% 485 4 Intermediate 0.07834 141 87.30% 193 1 Terminal -0.08282 62 86.64% 196 6 Intermediate -0.07834 143 87.55% 229 6 Intermediate -0.08282 62 86.61% 328 4 Intermediate -0.08673 193 86.61% 328 4 Intermediate -0.08039 114 85.96% 229 3 Intermediate -0.08049	146	99.25%	409	1	Terminal	-0.00030	Suppor		0.43203 1 EE/EC		1 19064		
154 0001x 00 3 intermediate 0.00176 164 87.75% 99 5 intermediate 0.00176 218 87.74% 485 4 intermediate 0.00176 231 87.54% 146 4 intermediate 0.007834 141 87.30% 193 1 Terminal 0.008282 62 86.64% 196 6 intermediate 0.008393 193 96.51% 328 4 intermediate 0.008024 161 85.95% 229 3 intermediate 0.008178 114 85.95% 229 3 intermediate 0.008178	190	00.23%	403	2	Intermediate	0.00202			1.00400		0.13064		
Indim Official Official Official Official Official Official Official 218 87.74% 146 4 Intermediate 0.07911 231 87.54% 146 4 Intermediate 0.07913 141 87.30% 193 1 Terminal 0.08282 62 86.84% 196 6 Intermediate 0.080573 193 86.51% 328 4 Intermediate 0.08024 161 85.96% 275 4 Intermediate 0.08109 114 85.95% 229 3 Intermediate 0.08109	164	97.76%	99	5	Intermediate	0.09176	N N		0.46726		0,20000		
210 01.14% 40.5 4 Intermediate 0.07834 141 87.54% 146 4 Intermediate 0.07834 141 87.30% 193 1 Terminal 0.08282 62 96.64% 196 6 Intermediate 0.08039 32 86.65% 179 5 Terminal 0.08573 193 86.51% 328 4 Intermediate 0.08074 161 85.96% 275 4 Intermediate 0.08049 114 85.95% 229 3 Intermediate 0.08409	218	87.74%	/95	3	Intermediate	0.07911	Mean Chil Day		0.46723		0.30000		
141 87.302 193 1 Terminal -0.08292 62 86.64% 196 6 Intermediate -0.08393 92 86.62% 179 5 Terminal -0.08024 161 85.96% 275 4 Intermediate -0.08024 161 85.95% 229 3 Intermediate -0.08078 114 85.95% 229 3 Intermediate -0.08078	231	87 54%	146	4	Intermediate	-0.07834	Sta. De	v.	0.0002		0.40000		
101 01.04% 136 1 1 0.08839 92 86.62% 179 5 Terminal -0.08573 193 96.51% 328 4 Intermediate -0.08024 161 85.95% 275 4 Intermediate -0.08178 114 85.95% 229 3 Intermediate -0.08409 ▼	141	87 30%	140	4	Terminal	.0.08282							
32 36.62% 179 5 Terminal -0.08573 193 36.51% 328 4 Intermediate -0.08074 161 85.96% 275 4 Intermediate 0.08178 114 85.95% 229 3 Intermediate 0.08409 ▼	62	86.84%	196	6	Intermediate	-0.08839							
193 86.51% 328 4 Intermediate 0.009024 161 85.96% 275 4 Intermediate 0.08178 114 85.95% 229 3 Intermediate -0.08409 ✓	92	86.62%	179	5	Terminal	-0.08573							
161 85.96% 275 4 Intermediate 0.00178 114 85.95% 229 3 Intermediate -0.08409 ▼	193	86.51%	328	4	Intermediate	-0.08024							
114 95.95% 229 3 Intermediate -0.08409 -	161	85.96%	275	4	Intermediate	0.08178							
	114	85.95%	229	3	Intermediate	-0.08409 -1							
		00.00%	225	5									
p	4												

Recall that the RuleLearner compression method decomposes a TreeNet model into a collection of individual nodes (internal and terminal) and then harvests individual nodes using GPS. Each node represents a segment of the original data described by a collection of rules leading into this node. Hence, analyzing the rules associated with the top selected nodes might provide additional modeling insights.

The nodes are listed on the left part of the **Explore** window according to the order of their importance (as reported by the GPS component). The actual rules associated with the currently selected node (segment) are shown on the top right part while the basic stats about the node (segment) are shown on the bottom right part of the window.



Important Rule Metrics

Note the use of the following terms generally accepted in the associative rules research community:

- **Support** fraction of the sample (either learn or test) covered by the segment.
- Lift segment mean of the target divided by the overall sample mean of the target.
- In the case of binary target, this is the same as segment fraction of 1s divided by the sample fraction of 1s.
- Mean, Std. Dev. the usual statistical definitions of the mean and standard deviation in the segment of interest.

Click on the [Rules Table] button to open up even more detailed information about each node. The resulting table can be sorted by clicking on any of its columns. This allows quick and easy identification of the potential rules of interest. For example, you may focus on finding the segments having the highest test sample lift or segments having the highest support and so on.

For example, internal node 4 of tree 241 is at the top of the importance list, it covers almost 50% of the available data (very large support) and is described by a joint collection of rules involving POST_BIN, OCCUP_BLANK, and GENDER.

#	Importance	Tree Number	Node Number	Terminal	Coefficient	Support Learn	Support Test	N Learn	N Test	Mean Learn	Mean Test	Lift Learn	Lift Test	Std. Dev. Learn	Std. Dev. Test	Split 1	Split 2	Split 3
45	100.00%	241	4	Intermediate	0.09021	0.43289	0.49630	229	67	0.46725	0.38806	1.55456	1.19064	0.50002	0.49099	POSTBIN >= 3.50000 or F	OCCUP_BLANK < 0.5000	GENDER is not missing
91	95.94%	172	4	Intermediate	0.08584	0.48015	0.55556	254	75	0.37008	0.37333	1.23127	1.14545	0.48378	0.48695	MARITAL\$ is in { "Married		
104	93.49%	203	5	Intermediate	0.08496	0.58979	0.64444	312	87	0.38782	0.36782	1.29030	1.12853	0.48804	0.48501	CREDIT_LIMIT < 54500.0	INCOME < 7166.50000 ar	POSTBIN >= 1.50000
100	92.33%	416	2	Terminal	-0.08511	0.37807	0.37778	200	51	0.34000	0.41176	1.13119	1.26337	0.47490	0.49705	INCOME < 3697.50000 ar	HH_SIZE is not missing	AGE is not missing
147	92.29%	393	2	Intermediate	0.08261	0.47448	0.51111	251	69	0.40637	0.43478	1.35203	1.33399	0.49214	0.49936	CREDIT_LIMIT < 7675.00		
132	92.22%	370	7	Intermediate	-0.08292	0.44612	0.45185	236	61	0.22881	0.24590	0.76127	0.75447	0.42096	0.43419	OWNRENT\$ is in { "Parer	AGE is not missing	AGE < 38.50000
107	91.95%	315	1	Terminal	-0.08468	0.37996	0.52593	201	71	0.14428	0.19718	0.48002	0.60499	0.35225	0.40070	CREDIT_LIMIT < 26684.5	TIME_EMPLOYED < 1.25	N_INQUIRIES < 2.500
135	91.62%	367	1	Terminal	0.08288	0.42344	0.44444	224	60	0.19643	0.20000	0.65353	0.61364	0.39819	0.40338	OWNRENT\$ = "Parents"	N_INQUIRIES < 6.50000	
96	91.52%	227	4	Intermediate	-0.08537	0.35728	0.40000	189	54	0.20635	0.16667	0.68653	0.51136	0.40576	0.37618	AGE is not missing	AGE < 30.50000 and AGE	INCOME >= 2330.500
145	91.43%	183	5	Intermediate	-0.08262	0.57278	0.52593	303	71	0.23762	0.28169	0.79058	0.86428	0.42633	0.45302	INCOME >= 2061.50000 c	AGE is not missing	AGE < 35.50000
151	91.29%	115	e	Terminal	-0.08236	0.43289	0.35556	229	48	0.23581	0.27083	0.78454	0.83097	0.42543	0.44909	AGE is not missing	INCOME >= 1865.50000 c	HH_SIZE is not missin
67	91.12%	370	4	Intermediate	0.08821	0.30813	0.30370	163	41	0.39264	0.43902	1.30632	1.34701	0.48984	0.50243	OWNRENT\$ is in { "Other	AGE is not missing	AGE < 42.50000
75	90.68%	222	4	Intermediate	0.08720	0.68431	0.68889	362	93	0.26243	0.29032	0.87312	0.89076	0.44056	0.45637	AGE is not missing	AGE < 41.50000 and AGE	INCOME >= 2228.500
109	89.87%	29	3	Intermediate	0.08445	0.34594	0.33333	183	45	0.30055	0.28889	0.99993	0.88636	0.45975	0.45837	POSTBIN >= 2.50000 or F	CREDIT_LIMIT >= 6345.5	
56	89.20%	313	5	Intermediate	0.08900	0.27788	0.32593	147	44	0.40816	0.34091	1.35798	1.04597	0.49317	0.47949	CREDIT_LIMIT < 6818.50	INCOME >= 2560.50000 c	
210	88.67%	446	7	Terminal	0.07933	0.48015	0.55556	254	75	0.37008	0.37333	1.23127	1.14545	0.48378	0.48695	MARITAL\$ is in { "Married		
57	88.52%	439	1	Terminal	-0.08890	0.27221	0.20000	144	27	0.27778	0.25926	0.92418	0.79545	0.44947	0.44658	INCOME < 2907.50000 ar	EDUCATION\$ = "College"	
146	88.25%	409	1	Terminal	-0.08262	0.64839	0.77037	343	104	0.22157	0.27885	0.73719	0.85555	0.41591	0.45060	CREDIT_LIMIT < 43376.5	CREDIT_LIMIT < 23984.0	N_INQUIRIES < 5.500
194	88.01%	88	3	Intermediate	0.08015	0.40454	0.41481	214	56	0.33178	0.33929	1.10383	1.04099	0.47195	0.47775	POSTBIN >= 1.50000 or F	MARITAL\$ is in { "Other",	
	07 700		-		0.00470	0.0504.7		100	17	- 1010F	0.40000	4 40000	1 10013	0.10500	0.00103	LUUIDIDDA (PARA	1100011E 1000 E0000	ABER 11 117 ALB

Finally, click on the **[Support vs. Lift]** button to see the graphical representation of the usual tradeoff involved. Note that the larger support segments tend to have smaller lift.





This concludes our discussion of the ISLE model compression approach now available in SPM.

RuleLearner Example

At this point it will suffice to say that setting up a model compression run using ISLE from a user standpoint is very straightforward. We are essentially creating a "pipeline", a sequence of two already introduced engines, first a TreeNet engine using the original predictors followed by a GPS engine that uses a decomposed TreeNet model as its own inputs. The decomposition itself is done automatically by SPM based on the user-selected method, which could be either ISLE or RuleLearner (as well as additional trivial modifications introduced below). In addition, it is assumed that each engine component of the pipeline (TreeNet and GPS) is configured using its own set of control parameters as usual.

The end result of the compression pipeline is the overall compression summary plus the usual output of the TreeNet engine (as if it were run by itself) as well as the standard GPS output of the follow-up compression phase.

The output displays are deliberately designed for ease of comparison between the original uncompressed model and the resulting compressed model. The user can choose any desired model for viewing, scoring, and translation using the "point and click" approach thus balancing the degree of compression versus model size.

Setting up RuleLearner

Again, we start with the GOODBAD.CSV data set which is rather on the small side but runs very quickly and illustrates our main points well. The dataset comes from a credit default study and has 664 observations and 14 variables including a binary response variable named TARGET, with 1 indicating a bad credit standing account and 0 otherwise. The remaining predictors provide a nice mix of continuous and categorical measures which represent a typical modeling environment. The goal of the study is to build a predictive model for bad credit using the TreeNet approach and then possibly compress the model



using either ISLE or RuleLearner approaches.

Use the **File/Open/Data File...** menu item to open the GOODBAD.CSV dataset, then click the **[Model...]** button in the resulting activity window to open the **Model Setup** window.

In the Model tab:

- Set Analysis Engine to RuleLearner this activates the pipeline part of the SPM the RuleLearner tab. Note that this mode activates the TreeNet tab and the GPS and GPS Advanced tabs thus giving you full control over other parts of the pipeline.
- Set Sort: to File Order this sorts all variables according to the position in the dataset.
- Check TARGET variable as the Target.
- Check all remaining variables as predictors.
- Select **Target Type** to **Classification/Logistic Binary** to take advantage of the natural capability of both TreeNet and GPS engine to handle binary targets effectively.

GPS Model	GPS Advanced Categorical	RuleLeamer Testing	Cost: Select C	ases	Class Weig TreeNet	hts Per Plots&	nalty Options	Li TN Ad	ags Ivanced	TN Interactions		
	Γ		١	/ariable !	Selection							
	Variable N	lame		Target	Predictor	Categorical	ical Weight		Target Type Classification/			
ARGET			~					Log	istic Binary			
GE									O Reg	pression		
REDIT_LI	МІТ				V				C Uns	upervised		
DUCATIO	N\$				~	~						
ENDER					V				Set F	ocus Class		
H_SIZE					~							
NCOME					✓				Tar	at Variable		
ARITAL\$					✓	•			Targ			
INQUIRI	ES				~			-				
				Coloct	C.	Select -			Wei	ght Variable		
ort: File Or	rder 🗾			Predictors Cat.								
Filter									Numbe	r of Predictors		
All/Sele	cted Characte	er C Numeric								13		
omatic Bes	st Predictor Discover	у ———				Nu	mber of Pr	redicto	rs in Mode	el: 13		
Off			A	fter Build	ling a Mode		nalysis Eng	jine —				
Discover o	nly			Save Grove RuleLearner						-		
			_									

Switch to the Testing tab, and make sure that **Fraction of cases selected at random for testing** is set to 0.2.

We now need to set up the TreeNet component of the pipeline, as if you were setting up a stand-alone TreeNet model.

- Set the Learn Rate to 0.05.
- Set the Number of trees to 500.
- Set the Optimal Logistic Model Selection Criterion to ROC area.
- Leave the remaining controls at their defaults (consult with the screenshot below).
- ✓ See the TreeNet chapter for detailed description of all of the available controls.



Model Setu	p									
GPS	GPS Advanced	RuleLearner	Costs	Class Weights	Penalty	Lags]			
Model	Categorical	Testing	Select Cases	TreeNet	Plots&Options	TN Advanced	TN Interactions			
	Γ		TreeN	let Options						
	TreeNet Loss Fu	nction					-1			
	Classification/L	ogistic Binary	_			Configure				
	Criterion Determ	ining Number of	Trees Optimal fo	r Logistic Model						
	C Cross Entro	py (Likelihood)	ROC are	a 🛛 🔿 Lift in	given proportion o	of 0.100				
	C Classificatio	n Accuracy. Clas	sify cases as Tar	rget Class if Probab	pility Exceeds	0.500				
	Overfitting Prote	ction		Limits						
	Learn Rate:	Auto 0.	0500 -	Num	iber of trees to bi	uild: 500 _				
	Subsample fi	action:	0.50	Max	imum nodes per tr	ree: 6	3			
	Random			Terminal node Minimum Training 10 -						
	Predictors pe	r node:	6	Influence trimming speed-up						
	Vary tree size	es randomly (As	Poisson)	Total Influence fraction: 0.10						
	☐ Model Varian separately	ce-Dispersion co	mpoment	Std. Defaults	Save Defaults	Recall Defau	lts			
Automatic Be:	st Predictor Discover	у ———			Number of F	Predictors in Mod	el: 13	-		
i Off			After B	uilding a Model	Analysis En	igine				
Discover o	nly Maximum v	ariablec en en en e	Sa	ve Grove	RuleLearr	ner	•	I		
) Discover a	nd run for each cla	iss 8			Cancel	Continu	Je Start			

Next you may want to set up the GPS component of the pipeline using the **GPS** and **GPS** Advanced tabs. The default settings in those tabs are good enough for our purposes, you may however, review the GPS part of the manual and later experiment with different number of steps, points, as well as elasticities and learn rates. Finally, switch to the ISLE tab to setup the actual pipeline "linkage" parameters, which could be as simple as specifying whether you want ISLE or RuleLearner compression or both (Pooled ISLE and Node Predictors).



Model Setup						×
Model Categorical Testing Se GPS GPS Advanced RuleLearner) Select Cases mer Costs C		Plots&Options Penalty	TN Advanced Lags	TN Interactions	1
Pure Tree-Based Models TreeNet Model compression (ISLE) RuleLearner: Extract Rules from TreeNet Pool ISLE and Node Predictors	Estimated P 500 5000 5500	redictor Counts (one p (one p (both	redictor per tree) redictor per node trees and nodes a) :) are predictors)		
Hybrid Tree-regression Models None Include Original Predictors in models selected Records with missing values will be deleted Run models both ways (with and without original Notes and the selected of the selected	l above nal predictors)	Rules Rep Max Rules Save Res	orting and Saving to report: 10 ults to	g (RuleLearner) -		
Automatic Best Predictor Discovery	After Buik	ding a Model	Number of I Analysis Er RuleLearn Cancel	Predictors in Mode ngine ner	el: 13 v Je Start	

Note that we have requested only the RuleLearner rule extraction feature which will trigger only one independent compression runs after the initial TreeNet model has been built: you could always try one run for the ISLE compression and the other to try the RuleLearner compression like what we showed earlier for the ISLE algorithm which would give you the convenience of not building the TreeNet model (the first stage of the pipeline) twice and thus saving the overall run time.

The control options on the RuleLearner tab under the Pure Tree-Based Models section are:

- TreeNet Model Compression (ISLE) uses tree-based variables as intermediate inputs to the GPS compression stage.
- RuleLearner: Extract Rules from TreeNet uses node-based variables as intermediate inputs to the GPS compression stage.
- Pool ISLE and Node Predictors technically a hybrid approach, uses the combined set of both tree-based and node-based variables as intermediate inputs to the GPS compression stage. Note that the end result of this could be a compressed model that has both types of components.
- Estimated Predictor Counts reports the total number of intermediate variables that will be created during the pipeline process. Note that the RuleLearner approach dramatically increase the memory and computational burden of the process, use it judiciously!
- Hybrid Tree-regression Models allows to include the original predictors into the intermediate set of inputs to the GPS compression stage. This sometimes helps to compress the model even further in the presence of strong linear effects.
- Keep in mind that each pipeline mode, especially when it involves the node-based variables (RuleLearner) may take significant amount of run time. It is best to start experimenting with a single ISLE or RuleLearner model first and then proceed with more elaborate setups.
- Max Rules to Report sets the default number of the top important rules that will be reported and saved.
- [Save Results to] click this button if you want to save the top important rules into a file.



Press the [Start] button to initiate the modeling pipeline.

Depending on your prior system settings, the following window may occur:

Salford Predictive Modeler v7.0
Discrete variables were discovered that have one or more levels not encountered in all data partitions. All levels not seen in the training data are mapped to "missing" in test
Do not show this message again.
ОК

This indicates that some of the categorical predictors available in the dataset had under-represented categories that could not be assigned to both learn and test partitions. You may ignore this warming for now and press the **[OK]** button to proceed with the modeling run.

As the run develops, you will first see the TreeNet engine progress report followed by the GPS engine progress report for the ISLE run and then again for the RuleLearner run. This indicates that the two separate pipelines are being properly executed.



Viewing RuleLearner Results

A successfully finished compression run with one pipeline will produce the **Pipeline Results: TreeNet Rule Extraction with RuleLearner** Results: Model summary window shown below:



In our case, two different models are reported:

- Original the original best TreeNet model before compression.
- RuleLearner best model using RuleLearner (node-based variables) approach.



Translating RuleLearner

Press the [Translate...] button to activate the RuleLearner Model Translation control window.

	C: \Users \Jenovo \	AppData \Local \Temp \sm2g_00050.grv
elect model to tran	slate: Pipeline RuleLear	rner - Binary Classification - Target: TARGET
elect Specific Mode		
elected: GPS: El	asticity 2, Point #200, NC	oeff=2789, ROC (Area Under Curve): 0.905844 Optimal Select.
ave Output To File		
Save Output	4s	
anguage or Text re	port	SAS Options
SAS	C Classic	Node Rules Only: 10 Top Rules
Сc	C History	
-	C Rules	
		Begin label: MODELBEGIN Done label: MODELDONE
C PMML C Java	C Plots	
C PMML C Java	C Plots	Node prefix: NODE

Use the **Select Specific Model** selection box to pick the model of interest (the Original, ISLE, or RuleLearner).

Press the **[Select...]** button in the **Select Specific Model** section if you want to pick a different model on the GPS path for the current compression approach.

The rest of the translation controls have been described earlier in the manual.

Press the **[OK]** button to initiate the model translation process.





Viewing RuleLearner Details

This window shows detailed RuleLearner compression results indexed by model size in nodes. The two test sample performance curves are aligned such that one can easily compare the performance of two models with identical size.

Note that the 2789-node TreeNet model has test ROC 0.875 while the 2789-node RuleLearner compressed model has ROC 0.90584. Even though both models have identical number of nodes, they differ in the actual trees selected. The TreeNet model takes the first consecutive trees from the TreeNet sequence (all combined with the unit coefficients and the original node updates) while the RuleLearner model takes some specific subset of 2789 nodes from the original complete set available in the sequence. Furthermore, each selected node has a new associated update.

✓ The actual subset of nodes can be determined by looking into the RuleLearner Details or translating the model.

The top part of the window reports basic stats on the optimal TreeNet model versus optimal RuleLearner model in terms of ROC performance.



✓ You can switch to alternative performance measures using the Performance Measure: selection box.

Press the [TreeNet Details] button to open the usual TreeNet Output window described in the TreeNet



engine chapter of this manual.

Press the **[RuleLearner Details]** button to open the usual **GPS Results** window described in the GPS engine chapter of this manual.

✓ Note that the GPS component of the RuleLearner pipeline uses nodes as input variables. Therefore, all parts of the GPS output windows referencing the predictors (Coefficients, etc.) will now report names like Tree 1 Node 1, Tree 1 TNode 1, Tree 2 Node 1, etc.

The remaining control items are similar to what we have already described earlier except for the **[Rules...]** button which opens up a RuleLearner specific **Explore** window.

Exploring the Rules

Press the **[Rules...]** button in the **Pipeline Results: RuleLearner** window to open the **Explore RuleLearner** window shown below.

olore Ru	leLearner: Pipeline	Results 6				1			-
#	Importance ∇	Tree Number	Node Number	Terminal	Coefficient 🔺	# 1 Tree:	182 Node:	Terminal 4 Dep	oth: 5
1	100.00%	182	4	Terminal	-3.24855	Coefficient: -3.2485	Rel. Importance:	100.00% Importance:	1.1680
5	68.14%	115	5	Intermediate	1.65475				
8	61.18%	198	6	Intermediate	-1.43201	POSTBIN is in { 4, 5 }			
2	57.79%	173	5	Terminal	-2.58744	CREDIT_LIMIT >= 550	04.50000 or CREDIT_LIM	IT is missing	
7	47.76%	44	4	Terminal	-1.45546	CPEDIT LIMIT < 3550	0.00000 and CREDIT 1 IN	IOT missing ATT is not missing	
4	46.03%	81	4	Terminal	-1.91133	CALDER _LEMIT < 3550	0.00000 and CREDIT_EI	ar is not misality	
11	45.55%	192	2	Terminal	1.20472				
20	33.29%	190	1	Terminal	-0.89509				
24	32.78%	141	4	Intermediate	0.77579				
3	32.64%	111	2	Terminal	1.91299				
9	29.96%	186	3	Terminal	1.35737	J			
15	29.25%	117	5	Terminal	0.97022				Prev
10	28.47%	181	5	Terminal	1.25990				1107
6	27.43%	1	2	Terminal	-1.45847				
31	27.21%	38	5	Intermediate	0.71648			-	
39	26.99%	169	2	Intermediate	-0.63753		Learn	Test	
12	26.86%	115	2	Terminal	-1.15002	Support	0.15254	0.21805	
25	26.38%	180	6	Terminal	-0.77373	Lift	0.32984	0.62539	
40	26.16%	177	2	Terminal	-0.62111	N	81	29	
21	25.77%	183	3	Terminal	0.85484	Mean	0.09877	0.20690	
17	25.68%	149	2	Terminal	0.92112	Target Std. Dev.	0.30021	0.41225	
13	25.34%	74	5	Intermediate	0.98728	Rule Std. Dev.	0.35955	0.41292	
33	24.60%	161	4	Terminal	-0.68687				
16	24.36%	193	4	Terminal	-0.94927				
32	24.00%	185	3	Terminal	-0.70900				
28	23.32%	63	3	Terminal	-0.73268				
27	23.08%	194	3	Terminal	-0.73511				
51	22.88%	155	3	Intermediate	0.53449 🔻				
ision:	5 🕂 Rule	Learner Details	reeNet Details	Rules Table	Support vs. Lift	:	(Commands Translate.	Score Save

Recall that the RuleLearner compression method decomposes a TreeNet model into a collection of individual nodes (internal and terminal) and then harvests individual nodes using GPS. Each node represents a segment of the original data described by a collection of rules leading into this node. Hence, analizing the rules asociated with the top selected nodes might provide additional modeling insights.

The nodes are listed on the left part of the **Explore** window according to the order of their importance (as reported by the GPS component). The actual rules associated with the currently selected node (segment) are shown on the top right part while the basic stats about the node (segment) are shown on the bottom right part of the window.

Note the use of the following terms generally accepted in the associative rules research community:

- **Support** fraction of the sample (either learn or test) covered by the segment.
- Lift segment mean of the target divided by the overall sample mean of the target.
- In the case of binary target, this is the same as segment fraction of 1s divided by the sample fraction of 1s.



- Mean- the average of the target variable for records that satisfy the rule of interest
- **Target Std. Dev.** the usual standard deviation of the target variable for records that satisfy the rule of interest
- **Rule Std. Dev.:** also referred to as the "scale" of a rule and is given by $\sqrt{support * (1 support)}$ where support is the support for the rule of interest
- Importance = Rule Std. Dev. * |Coefficient|

Click on the [Rules Table] button to open up even more detailed information about each node. The resulting table can be sorted by clicking on the any of its columns. This allows quick and easy identification of the potential rules of interest. For example, you may focus on finding the segments having the highest test sample lift or segments having the highest support and so on.

For example, internal node 4 of tree 241 is at the top of the importance list, it covers more than 50% of the available data (very large support) and is described by a joint collection of rules involving POST_BIN, OCCUP BLANK, and GENDER.

#	Importance	Tree Number	Node Number	Terminal	Coefficient	Support Learn	Support Test	N Learn	N Test	Mean Learn	Mean Test	Lift Learn	Lift Test	Std. Dev. Learn	Std. Dev. Test	Split 1	Split 2	Split 3
45	100.00%	241	4	Intermediate	0.09021	0.43289	0.49630	229	67	0.46725	0.38806	1.55456	1.19064	0.50002	0.49099	POSTBIN >= 3.50000 or F	OCCUP_BLANK < 0.5000	GENDER is not missing
91	95.94%	172	4	Intermediate	0.08584	0.48015	0.55556	254	75	0.37008	0.37333	1.23127	1.14545	0.48378	0.48695	MARITAL\$ is in { "Married		
104	93.49%	203	5	Intermediate	0.08496	0.58979	0.64444	312	87	0.38782	0.36782	1.29030	1.12853	0.48804	0.48501	CREDIT_LIMIT < 54500.0	INCOME < 7166.50000 ar	POSTBIN >= 1.50000
100	92.33%	416	2	Terminal	-0.08511	0.37807	0.37778	200	51	0.34000	0.41176	1.13119	1.26337	0.47490	0.49705	INCOME < 3697.50000 ar	HH_SIZE is not missing	AGE is not missing
147	92.29%	393	2	Intermediate	0.08261	0.47448	0.51111	251	69	0.40637	0.43478	1.35203	1.33399	0.49214	0.49936	CREDIT_LIMIT < 7675.00		
132	92.22%	370	7	Intermediate	-0.08292	0.44612	0.45185	236	61	0.22881	0.24590	0.76127	0.75447	0.42096	0.43419	OWNRENT\$ is in { "Pare	AGE is not missing	AGE < 38.50000
107	91.95%	315	1	Terminal	-0.08468	0.37996	0.52593	201	71	0.14428	0.19718	0.48002	0.60499	0.35225	0.40070	CREDIT_LIMIT < 26684.5	TIME_EMPLOYED < 1.25	N_INQUIRIES < 2.500
135	91.62%	367	1	Terminal	0.08288	0.42344	0.44444	224	60	0.19643	0.20000	0.65353	0.61364	0.39819	0.40338	OWNRENT\$ = "Parents"	N_INQUIRIES < 6.50000	
96	91.52%	227	4	Intermediate	-0.08537	0.35728	0.40000	189	54	0.20635	0.16667	0.68653	0.51136	0.40576	0.37618	AGE is not missing	AGE < 30.50000 and AGE	INCOME >= 2330.5000
145	91.43%	183	5	Intermediate	-0.08262	0.57278	0.52593	303	71	0.23762	0.28169	0.79058	0.86428	0.42633	0.45302	INCOME >= 2061.50000	AGE is not missing	AGE < 35.50000
151	91.29%	115	6	Terminal	-0.08236	0.43289	0.35556	229	48	0.23581	0.27083	0.78454	0.83097	0.42543	0.44909	AGE is not missing	INCOME >= 1865.50000 c	HH_SIZE is not missing
67	91.12%	370	4	Intermediate	0.08821	0.30813	0.30370	163	41	0.39264	0.43902	1.30632	1.34701	0.48984	0.50243	OWNRENT\$ is in { "Othe	AGE is not missing	AGE < 42.50000
75	90.68%	222	4	Intermediate	-0.08720	0.68431	0.68889	362	93	0.26243	0.29032	0.87312	0.89076	0.44056	0.45637	AGE is not missing	AGE < 41.50000 and AGE	INCOME >= 2228.5000
109	89.87%	29	3	Intermediate	0.08445	0.34594	0.33333	183	45	0.30055	0.28889	0.99993	0.88636	0.45975	0.45837	POSTBIN >= 2.50000 or F	CREDIT_LIMIT >= 6345.5	
56	89.20%	313	5	Intermediate	0.08900	0.27788	0.32593	147	44	0.40816	0.34091	1.35798	1.04597	0.49317	0.47949	CREDIT_LIMIT < 6818.50	INCOME >= 2560.50000 c	
210	88.67%	446	7	Terminal	0.07933	0.48015	0.55556	254	75	0.37008	0.37333	1.23127	1.14545	0.48378	0.48695	MARITAL\$ is in { "Married		
57	88.52%	439	1	Terminal	-0.08890	0.27221	0.20000	144	27	0.27778	0.25926	0.92418	0.79545	0.44947	0.44658	INCOME < 2907.50000 ar	EDUCATION\$ = "College"	
146	88.25%	409	1	Terminal	-0.08262	0.64839	0.77037	343	104	0.22157	0.27885	0.73719	0.85555	0.41591	0.45060	CREDIT_LIMIT < 43376.5	CREDIT_LIMIT < 23984.0	N_INQUIRIES < 5.500
194	88.01%	88	3	Intermediate	0.08015	0.40454	0.41481	214	56	0.33178	0.33929	1.10383	1.04099	0.47195	0.47775	POSTBIN >= 1.50000 or F	MARITAL\$ is in { "Other",	
	07 7001		-		0.00470	0.0504.7		100		0.10105	0.10000	1 10000	1 10017	0.10500	0.00107	100000000000000000000000000000000000000	11001 IF 1000 F0000	

Finally, click on the **[Support vs. Lift]** button to see the graphical representation of the usual tradeoff involved. Note that the larger support segments tend to have smaller lift.





This concludes our discussion of the new model compression approaches now available in SPM.

